

miniPointe®

MiniPointe is a tiny agile air cutter specifically designed to produce sharp beam and aerial effects especially in venues constrained by size.

**Light source**

Osram Sirius HRI 140 W RO

**Light output**

4.960 lm, 400.000 lx @ 5m

**Zoom range**

3° fixed beam

**Effects**static gobo wheel, Dynamic Flower Effect,
Beam Shaper

Striking bright 0° parallel beams with glowing colours and static gobo wheel patterns can be multiplied by innovative Dynamic Flower Effect - DFE™ producing various different shapes of flower beams DFE™ dynamically changing in the air. Fine tuned short arc of the Osram Sirius HRI 140 W RO lamp and optimized optical system pushes with ease through haze and fog. Smooth variable frost filter and any one of the 13 rich colours is instantly ready to create a smooth even wash, extending the feature set of this petite but powerful Beam, Wash and Effect fixture.

Technical Specification

Source

- Lamp: Discharge short arc lamp with integrated reflector
- Approved model: Osram Sirius HRI 140 W RO
- Life time : 6.000 hours
- Lamp: Discharge short arc lamp with integrated reflector
- Approved model: Osram Sirius HRI 140 W RO
- Life time : 6.000 hours

Optical system

- Robe's proprietary optical design
- Beam angle:
 - 3° on full open/hole
 - 0.7° / 1.2° / 1.8° with beam reducers
- Robe's proprietary optical design
- Beam angle:
 - 3° on full open/hole
 - 0.7° / 1.2° / 1.8° with beam reducers

Dynamic Effects and Features

- Colour wheel: 13 dichroic filters + white
- Static Gobo wheel: 10 gobos + 3 beam reducers
- DFE™ - Dynamic Flower Effect - creating spectacular beam effects in the air which can change shape, size and speed of rotation (patent pending)
- Colour wheel: 13 dichroic filters + white
- Static Gobo wheel: 10 gobos + 3 beam reducers
- DFE™ - Dynamic Flower Effect - creating spectacular beam effects in the air which can change shape, size and speed of rotation (patent pending)

Control and programming

- Setting & Addressing: two-row LCD display & 4 control buttons
- Wireless CRMX™ technology from Lumen Radio: On request
- DMX Protocol modes: 3
- Setting & Addressing: two-row LCD display & 4 control buttons
- Wireless CRMX™ technology from Lumen Radio: On request
- DMX Protocol modes: 3

Movement

- Tilt movement: 270°
- Pan movement: 540°
- Controllable speed of Pan/Tilt movement
- Tilt movement: 270°
- Pan movement: 540°
- Controllable speed of Pan/Tilt movement

Static gobos

- Aluminium wheel with fixed gobos: 10 gobos & 3 beam reducers
- Aluminium wheel with fixed gobos: 10 gobos & 3 beam reducers

Thermal specification

- Maximum ambient temperature: 45 °C (113 °F)
- Maximum surface temperature: 75 °C (167 °F)
- Minimum operating temperature: -5 °C (23 °F)
- Maximum ambient temperature: 45 °C (113 °F)
- Maximum surface temperature: 75 °C (167 °F)
- Minimum operating temperature: -5 °C (23 °F)

Electrical specification and connections

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: 260 W at 230 V / 50 Hz
- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: 260 W at 230 V / 50 Hz

Approvals

- CE Compliant
- cETLus Compliant
- CE Compliant
- cETLus Compliant

Mechanical specification

- Height: 480 mm (19.9") - head in vertical position
- Width: 317 mm (12.5")
- Depth: 204 mm (8")
- Height: 480 mm (19.9") - head in vertical position
- Width: 317 mm (12.5")
- Depth: 204 mm (8")

Rigging

- Mounting points: 2 pairs of ¼-turn locks
- 2 x Omega brackets with ¼-turn quick locks
- Universal operating position
- Mounting points: 2 pairs of ¼-turn locks
- 2 x Omega brackets with ¼-turn quick locks
- Universal operating position

Included items

- User Manual
- User Manual

Optional accessories


- Lamp Osram Sirius HRI 140W RO: 14080051
- Wireless DMX external module: 10980127
- Mounting adapter for one omega holder: 10980100
- Lamp Osram Sirius HRI 140W RO: 14080051
- Wireless DMX external module: 10980127
- Mounting adapter for one omega holder: 10980100

Legal

- miniPointe® is a registered trademark of Robe lighting s. r. o.
- miniPointe® is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patents
- miniPointe® is a registered trademark of Robe lighting s. r. o.
- miniPointe® is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patents

Gobos&Colours


Colour Wheel



14070398



14070399




14070400




14070401



14070402




14070403



14070404



14070405



14070406




14070407



14070408



14070409



14070410

Fixed Gobo Wheel, Detail



99014355