

# Spikie®

Spikie, a small, super fast LED WashBeam, which utilises a single 60W RGBW light source with a specially designed 110mm wide front lens producing a solid beam. The fixture quickly zooms from a soft wide 28° wash to a tight sharp-edged 4° beam or one of two new stunning air effects.

**Light source**

60W RGBW LED

**Light output**

1.150 lm, 9.270 lx @ 5 m

**Zoom range**

4°-28°

**Effects**MCFE™ - Multi-Coloured Flower Effects,  
Colour Rainbow Effect, 3 Facet Prism

Robe patented MCFE™ - Multi-Coloured Flower Effects, creates sharp multicoloured spikes of light, rotating in both directions at variable speed. Additionally, a unique Beam Effect Engine transforms the output into a dynamic ray of three narrow beams, creating another new visual effect to the show. Continuous rotation of pan and tilt gives new dynamic elements across the stage. Spikie is a very compact 7.3 kg fixture, which can be hung in any position. It is supplied complete with one Omega bracket and is available in cardboard, single, quad and eight-pack cases.

# Technical Specification

## Source

- Light source: 60W RGBW LED
- LED life expectancy: min. 50 000 hours
- Typical lumen maintenance: L70/B50 @ 50.000 hours
- Light source: 60W RGBW LED
- LED life expectancy: min. 50 000 hours
- Typical lumen maintenance: L70/B50 @ 50.000 hours

## Optical system

- Robe's proprietary optical design
- High - efficiency zoom optical system, ratio 7:1
- Zoom range: 4° - 28°
- Robe's proprietary optical design
- High - efficiency zoom optical system, ratio 7:1
- Zoom range: 4° - 28°

## Dynamic Effects and Features

- Colour mixing mode RGBW or CMY
- Variable CTO: 2.700K - 8.000K
- Virtual Colour Wheel: with 66 preset swatches
- Colour mixing mode RGBW or CMY
- Variable CTO: 2.700K - 8.000K
- Virtual Colour Wheel: with 66 preset swatches

## Control and programming

- Setting & Addressing: two-row LCD display & 4 control buttons, stand-alone operation with 3 editable programs (each up to 40 steps)
- Protocols: USITT DMX-512, RDM
- Wireless CRMX™ technology from Lumen Radio: On request
- Setting & Addressing: two-row LCD display & 4 control buttons, stand-alone operation with 3 editable programs (each up to 40 steps)
- Protocols: USITT DMX-512, RDM
- Wireless CRMX™ technology from Lumen Radio: On request

## Movement

- Pan movement range 540° with continuous rotation control
- Tilt movement range 360° with continuous rotation control
- Movement control: Standard and Speed
- Pan movement range 540° with continuous rotation control
- Tilt movement range 360° with continuous rotation control
- Movement control: Standard and Speed

## Thermal specification

- Maximum ambient temperature: 45 °C (104 °F)
- Maximum surface temperature: 70°C (158°F)
- Minimum operating temperature: -5°C (23°F)
- Maximum ambient temperature: 45 °C (104 °F)
- Maximum surface temperature: 70°C (158°F)
- Minimum operating temperature: -5°C (23°F)

## Electrical specification and connections

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: Max. 100 W at 230 V / 50 Hz
- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: Max. 100 W at 230 V / 50 Hz

## Approvals

- CE compliant
- cETLus compliant
- CE compliant
- cETLus compliant

## Mechanical specification

- Height: 408 mm (16.1") - head in vertical position
- Width: 277 mm (10.9")
- Depth: 147 mm (5.8")
- Height: 408 mm (16.1") - head in vertical position
- Width: 277 mm (10.9")
- Depth: 147 mm (5.8")

## Rigging

- Mounting positions: Horizontally or vertically
- Universal operating position
- Mounting points: 1 pair of 1/4-turn locking points
- Mounting positions: Horizontally or vertically
- Universal operating position
- Mounting points: 1 pair of 1/4-turn locking points

## Included items

- User Manual
- Omega Adaptor CL-regular
- User Manual
- Omega Adaptor CL-regular

## Optional accessories

- Wireless DMX external module: 10980127
- Trigger Clamp Doughty: 17030386
- Safety wire 35 kg: 99011963 Mains Cable powerCON TRUE1 In/Schuko, 2m, Indoor 13052405
- Wireless DMX external module: 10980127
- Trigger Clamp Doughty: 17030386
- Safety wire 35 kg: 99011963 Mains Cable powerCON TRUE1 In/Schuko, 2m, Indoor 13052405

## Legal

- Spikie® is a registered trademark of Robe lighting s. r. o.
- Spikie® is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patents
- Spikie® is a registered trademark of Robe lighting s. r. o.
- Spikie® is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patents