

ROBIN® DLF Wash

This is the perfect companion to the ROBIN® DLX, the new ROBIN® DLF Wash is based on the same RGBW LED module. With a perfectly smooth output via the front Fresnel lens, this fixture has been optimized for those wanting an even light output with no shadows. (RGB breakups and shadows are not present even when on closely positioned trussing or other objects.)



Mechanical features include a newly designed linear motorized zoom of 5.5° - 60° and a diffusion filter for extension of the zoom up to 75°. The fixture uses an internal Barndoor module for creating different shapes. The module consists of four individually controllable blades and is rotatable by plus or minus 90 degrees.

Advanced software features include RGBW or CMY colour mixing, a set of calibrated whites, CTO, Tungsten lamp emulation (amber shift) and more.

Technical Specification

Source

- Light source: RGBW LED module
- LED module Life Expectancy: 20.000 hrs
- Light source: RGBW LED module
- LED module Life Expectancy: 20.000 hrs

Optical system

- Beam angle: 5.5° - 60° (75° with frost)
- RGBW or CMY colour mixing mode
- Beam angle: 5.5° - 60° (75° with frost)
- RGBW or CMY colour mixing mode

Electromechanical effects

- Four beam trimmers
- Beam trimmer module rotation +/-90°
- Frost effect: Separate, variable
- Four beam trimmers
- Beam trimmer module rotation +/-90°
- Frost effect: Separate, variable

Control and programming

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2
- Control channels: 29, 23, 21
- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2
- Control channels: 29, 23, 21

Internal barndoors

- Four individually controllable blades
- Rotation 0°-180° (all blades together)
- Four individually controllable blades
- Rotation 0°-180° (all blades together)

Thermal specification

- Maximum ambient temperature: 45 °C (104 °F)
- Maximum surface temperature: 90 °C (194 °F)
- Maximum ambient temperature: 45 °C (104 °F)
- Maximum surface temperature: 90 °C (194 °F)

Electrical specification

- Power supply: Electronic auto-ranging
- Input voltage range: 100-250 V, 50-60 Hz
- Max. power consumption: 550 W @ 230 V / 50 Hz (RGBW = full)
- Power supply: Electronic auto-ranging
- Input voltage range: 100-250 V, 50-60 Hz
- Max. power consumption: 550 W @ 230 V / 50 Hz (RGBW = full)

Mechanical specification

- Height: 681 mm (26.8") - head in vertical position
- Width: 432 mm (17.0")
- Depth: 483 mm (19.0") - head in horizontal position
- Height: 681 mm (26.8") - head in vertical position
- Width: 432 mm (17.0")
- Depth: 483 mm (19.0") - head in horizontal position

Rigging

- Mounting points: 2 pairs of ¼-turn locks
- 2x Omega brackets with ¼-turn quick locks
- Mounting points: 2 pairs of ¼-turn locks
- 2x Omega brackets with ¼-turn quick locks